Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A tracheostomy tube comprising:

a hollow tubular body having a proximal end portion, a distal end portion and a curved portion intermediate said proximal and distal end portions, said hollow tubular body including a collar at its proximal end, said collar having a groove; and

a flange situated at said proximal end portion, said flange being capable of selective attachment to said tubular body and removal therefrom, said flange extending radially from said proximal end portion when attached thereto, said flange including a cut-away portion extending radially inwardly from a lateral side thereof, said cut-away portion and said groove being cooperatively sized and shaped to mate when said flange is attached to said tubular body.

- 2. (canceled)
- 3. (previously presented) The tracheostomy tube of claim 1, wherein said flange is attachable to said tube by a snap-fit.
 - 4. (canceled)
- 5. (currently amended) The tracheostomy tube of claim 4 <u>1</u>, wherein at least one snap is provided at said cut-away portion to provide <u>said</u> <u>a</u> snap-fit with a receptacle on said tubular body.
- 6. (currently amended) The tracheostomy tube of claim 4 <u>1</u>, wherein said collar is integral with the hollow tubular body.
- 7. (currently amended) The tracheostomy tube of claim 4 <u>1</u>, wherein said collar includes one or more barbs for attaching the collar to said hollow tubular body.
- 8. (original) The tracheostomy tube of claim 1, further comprising a removable inner cannula insertable in said hollow tubular body.
- 9. (original) The tracheostomy tube of claim 1, wherein said hollow tubular body includes an inflatable cuff surrounding a part of said distal end portion, said

tracheostomy tube further comprising an inflation line connecting said cuff to a source of an inflation fluid.

- 10. (original) The tracheostomy tube of claim 9, wherein said inflation line is connected to said hollow tubular body along a length of said body, at least a portion of said inflation line being selectively peelable from said hollow tubular body.
- 11. (original) The tracheostomy tube of claim 10, wherein said hollow tubular body is trimmable along a trim line to reduce the length of said body, and said inflation line is peelable at least to a point below said trim line.
- 12. (currently amended) An insertion device comprising a tracheostomy tube and a loading dilator, the tracheostomy tube having a longitudinal bore and a tapered distal tip; the loading dilator having a larger-diameter stepped proximal portion and a smaller diameter distal portion extending from said larger diameter proximal portion, said smaller diameter distal portion having a generally cylindrical profile, said generally cylindrical profile tapering to and having a tapered distal end, the smaller-diameter distal portion being sized to be insertable through the longitudinal bore of said tracheostomy tube such that said tapered distal end extends axially beyond the tapered distal tip of the tracheostomy tube, the tracheostomy tube having a proximal end and further comprising a stop portion at said proximal end for engaging a distal portion of the larger-diameter stepped portion of the dilator to limit axial movement of the loading dilator through the tracheostomy tube.
- 13. (original) The insertion device of claim 12, wherein said stop portion comprises a collar provided at said proximal end of said tracheostomy tube.
- 14. (original) The insertion device of claim 12, wherein said stop portion comprises a larger-diameter proximal end portion of the tracheostomy tube.
- 15. (previously presented) The insertion device of claim 12, wherein said tapered distal end of said dilator is complementary to the tapered distal tip of the tracheostomy tube such that a generally smooth conical insertion tip is defined thereby.
- 16. (original) The insertion device of claim 15, wherein said generally smooth conical insertion tip has a profile sufficient for dilating an opening in the body of a patient for insertion of said tracheostomy tube.

17. (original) The insertion device of claim 12, wherein said larger-diameter stepped proximal portion of the dilator comprises a gripping surface.

- 18. (original) The insertion device of claim 17, wherein said gripping surface is formed from one or more polymers.
- 19. (original) The insertion device of claim 17, wherein said gripping surface is formed from a member selected from the group consisting of lower durometer urethanes, thermoplastic rubbers, thermoplastic elastomers and non-thermoplastic elastomers.
- 20. (original) The insertion device of claim 12, wherein said dilator largerdiameter stepped proximal portion and smaller diameter distal portion comprise integral molded components.
- 21. (original) The insertion device of claim 12, wherein said larger-diameter stepped proximal portion of said dilator includes a longitudinal passageway, and a portion of said smaller diameter distal portion is securely received within said longitudinal passageway.
- 22. (currently amended) A device for percutaneous insertion into the trachea of a patient, comprising:

a tracheostomy tube having a longitudinal passageway therethrough, said tracheostomy tube having a distal end portion percutaneously insertable into said trachea and a proximal end portion exterior to the trachea when said distal end portion is inserted; said tracheostomy tube further having a radially extending flange capable of selective attachment to and removal from said tracheostomy tube after said distal end portion has been inserted into the trachea;

a dilator positionable within said longitudinal passageway of said tracheostomy tube for dilating an opening in said trachea for insertion of said tracheostomy tube; and

a locking assembly for locking the tracheostomy tube to the dilator during insertion of said tracheostomy tube into the trachea, said locking assembly comprising a securement member associated with the dilator, said securement member engageable with a complementary member on said tracheostomy tube; the locking assembly further comprising a stop member disposed on an outer surface of the dilator, said stop member engaged with said dilator such that substantial axial movement of said stop member

along said dilator is prevented when an axial force is applied to said stop member, said stop member positioned on said outer surface and engageable with said securement member and said complementary member for preventing excess penetration of the tracheostomy tube into the trachea.

- 23. (canceled)
- 24. (canceled)
- 25. (currently amended) The device of claim 24 22, wherein said stop member comprises an annular ring integral with said dilator.
- 26. (currently amended) The device of claim 24 22, wherein said stop member comprises an annular ring fitted on the outer surface of said dilator.
- 27. (currently amended) The device of claim 24 22, wherein said complementary member comprises a collar integral with said tracheostomy tube.
- 28. (currently amended) The device of claim 24 22, wherein said complementary member comprises a collar fitted on an exterior surface of said tracheostomy tube.
- 29. (currently amended) The device of claim 24 <u>22</u>, wherein said securement member comprises a cap member having one or more screw threads engageable with said complementary member for locking said tracheostomy tube to said dilator.
 - 30. (canceled)
 - 31. (canceled)
- 32. (previously presented) The insertion device of claim 12, wherein said loading dilator has a central lumen extending substantially therethrough.